

MINING safety shoes

PRODUCT SHEET



ADV™ JUBATUS 6112

High-compliance S3 safety boots for demanding industrial environments, featuring penetration resistance, water resistance, for long-term use with quick lace system

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**



- S3** support :
- **construction**
 - **mining (BEST)**
 - **oil & gas**

Brand	Cheetah
Product Line	ADV
Product Name	Jubatus Sand
Description	Ankle Boots with Quick-Lace™
Sizes	4 - 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	665 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top / Bottom	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™
Tongue Lining	goremesh polyester DryMax™
Collar Lining	goremesh polyester

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Back strap	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A (Taupe) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)



- Lightweight composite toe protection**
- Enhanced shock absorption for all day comfort**
- Metal free nail-proof midsole**
- PU Insole improves heel cushioning**
- Water resistant upper keeps feet dry**

***available : custom label logo/emboss**

ADV NYX 6012

Low-cut S3 safety shoes to enhanced mobility, suitable for professionals requiring safety compliance without compromising movement.



S3



support :

- construction
- mining (BEST)
- oil & gas

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**

Brand	Cheetah
Product Line	ADV
Product Name	NYX
Description	Ankle Boots with Quick-Lace™ System
Sizes	4 – 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free nail proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	651 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™ gore
Tongue Lining	mesh polyester DryMax™ gore
Collar Lining	mesh polyester

Standard Compliance

	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Webbing	12mm Black/Silver Reflective
Insole	Ibisafe 31 Conductive White 2.8mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



*available : custom label logo/emboss

Supplied & supported by Swarna Safety for industrial projects and export markets.

NITRILE 2288

Heavy-duty safety boots equipped with nitrile rubber outsole, high heat resistance, and superior oil and chemical resistance for extreme industrial environments.



S1/S1P*



support :

- construction
- mining
- oil & gas (BEST)

- Nitrile Rubber • Steel SafetyToe
- Heat Resistant (Up to 300 C)
- Chemical Resistant Outsole

Brand	Cheetah
Product Line	Nitrile
Product Name	Nitrile
Description	Pull Up " Rigger " Boots
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	800 grams

Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back Counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Binding	Pvc R 38 Brown Backing TPE 0.8 mm
Quarter Label	Label Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A 16.6 MQ (0.1 – 1000 MQ Std)
Antistatic	Suitable
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



Steel toe protects from impact and compression



Strong and durable nitrile rubber outsole



Heat resistant up to 300 C



Acid and alkali resistant soles



PU Insole improves heel cushioning



- *additional steel midsole is available
- *available : custom label logo/emboss

Supplied & supported by Swarna Safety for industrial projects and export markets.

NITRILE 2290

Specialized **welding** safety boots designed with heat-resistant outsole and protective upper construction to reduce exposure to sparks, molten metal, and hot debris.



S1/S1P*

support :

- **construction**
- **mining**
- **oil & gas**

- **Nitrile Rubber**
- **Heat Resistant (Up to 300 C)**
- **Steel SafetyToe**
- **Chemical Resistant Outsole**

Brand	Cheetah
Product Line	Nitrile
Description	Welder Boots with adjustable velcro straps
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	750 grams

Upper Material

Vamp	Buffalo Suede Leather 1.8-2.0 mm Black
Quarter	Buffalo Suede Leather 1.8-2.0 mm Black
Back strap	Buffalo Suede Leather 1.8-2.0 mm Black
Back Counter	Buffalo Suede Leather 1.8-2.0 mm Black
Strap In	Buffalo Suede Leather 1.8-2.0 mm Black
Strap Out	Buffalo Suede Leather 1.8-2.0 mm Black
Tongue	Buffalo Suede Leather 1.0-1.2 mm Black

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Reflective	Reflective Silver
Velcro	Velcro Hook / Loop
Collar Padding	24 mm Foam Density 30
Webbing	Webbing Cheetah Black / Red
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

-  **Steel toe protects from impact and compression**
-  **Strong and durable nitrile rubber outsole**
-  **Heat resistant up to 300 C**
-  **Acid and alkali resistant soles**
-  **PU Insole improves heel cushioning**



REBOUND 7288

Traditional rigger-style safety boots featuring pull-on design, steel toe protection, and robust leather construction for outdoor industrial work.



S1/S1P*



support :

- construction (BEST)
- mining
- oil & gas

- DoublePU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Pull up 'Rigger' Boots
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
Weight (Size 7 half pair)	705 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Top Binding	Pvc R 38 Brown Backing TPE 0.8
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 Clearance 16.5 mm (> 14mm Std)
Toe Impact 200 Joules	mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Black
Hardness	Out sole : 62 - 68 Shore A (Black) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

***additional steel midsole is available (S1P edition)**

***available : custom label logo/emboss**



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



REBOUND 7106 H

Designed for daily industrial use, combining steel toe protection, durable full grain leather, and dual density PU outsole to **support long working hours on mixed surfaces.**



S1/S1P*

support :

- **construction (BEST)**
- **mining**
- **oil & gas**

- **DoublePU Outsole**
- **Steel Midsole (Optional)**
- **SteelSafety Toe**
- **Durable Grain Upper**

Brand	CHEETAH
Product Line	Rebound
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	667 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Tongue	Full Grain Buffalo Leather 1.0-1.2 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 Clearance 16.5 mm (> 14mm Std)
Toe Impact 200 Joules	mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Accesoris	D Ring
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A (Gray) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



***additional steel midsole is available (S1P edition)**

***available : custom label logo/emboss**