

LIGHT DUTY safety shoes

choices



REVOLUTION 3180

Affordable ankle-height safety boots offering **basic protection** and improved ankle support for general industrial use.



S1/S1P*

support :

- **construction**
- **warehouse**
- **office**

- **Single PU Outsole**
- **Steel Safety Toe**
- **Steel Midsole (Optional)**
- **Economical Pricing**

Brand	CHEETAH
Product Line	Revolution
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

UpperMaterial

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ (0.1 – 1000 MΩ Std) Wet: 20.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Slip resistant outsole



- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

REVOLUTION 3002 H

Affordable low-cut safety shoes providing essential protection and comfort for general industrial, warehouse, and support operations.



S1/S1P*

support :

- construction
- warehouse
- office

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing

Brand	CHEETAH
Product Line	Revolution
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

Upper Material

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ (0.1 – 1000 MΩ Std) Wet: 20.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

- *additional steel midsole is available
- *available : custom label logo/emboss



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Slip resistant outsole



CHEETAH Reflex™ 8083

Lightweight low-cut safety shoes featuring breathable materials for improved airflow, all-day comfort, and reliable protection in indoor and light industrial environments.



S1/S1P*

support :

- construction
- warehouse
- office

- DoublePU Outsole •
- Composite Safety Toe •
- SoleGard™
- Water Resistant

Brand	Cheetah
Product Line	Reflex
Product Name	Reflex 8083
Description	Lace up Sport Safety Shoes
Sizes	5 – 12 (UK)
Last	701 F
Safety Toecap	Composite Fiberglass
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	Insock Foam Red Black 150
Weight (Approx. Size 7)	498 grams

Upper Material

Vamp	Textile Knit Upper Cheetah Grey
Eyestay	Danaces Black Translucent Danaces
Eyestay Backer	Black Translucent
Toe bumper	PU Coated Leather Black 1.8-2.0 mm
Heel bumper	PU Coated Leather Black 1.8-2.0 mm
Lace	Lace 5mm Lime
Webbing	20 mm CHEETAH Black / Lime
Reinforce	Nonwoven Black
Emboss / Printing	" R " Toe Bumper

Lining

Vamp Lining	Grey polyester
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 P SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6mm (>14mm Std)

Miscellaneous

Collar Padding	8 mm Foam
Insole	Ibisafe 31 Conductive White 3.6mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Lime
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Nail Proof SoleGard™ Midsole



PU Insole improves heel cushioning



Breathable AirKnit™ Upper