

# HEAVY DUTY safety shoes *choices*



# NITRILE 2288

**Heavy-duty** safety boots equipped with **nitrile rubber** outsole, **high heat resistance**, and superior oil and chemical resistance for extreme industrial environments.



**S1/S1P\***

support :

- **construction**
- **mining**
- **oil & gas (BEST)**

- **Nitrile Rubber**
- **Heat Resistant (Up to 300 C)**
- **Steel SafetyToe**
- **Chemical Resistant Outsole**

|                         |                                  |
|-------------------------|----------------------------------|
| Brand                   | Cheetah                          |
| Product Line            | Nitrile                          |
| Product Name            | Nitrile                          |
| Description             | Pull Up " Rigger " Boots         |
| Sizes                   | 4 – 12 ( UK )                    |
| Last                    | 130                              |
| Safety Toecap           | Steel                            |
| Nail Protection         | Optional                         |
| Sole                    | Nitrile                          |
| Insock                  | <b>AIRGO PUTM Comfort Insole</b> |
| Weight (Approx. Size 7) | 800 grams                        |

### Upper Material

|               |  |
|---------------|--|
| Vamp          | Full Grain Buffalo Leather 1.8-2.0 Brown |
| Front Quarter | Full Grain Buffalo Leather 1.8-2.0 Brown |
| Rear Quarter  | Full Grain Buffalo Leather 1.8-2.0 Brown |
| Back Counter  | Full Grain Buffalo Leather 1.8-2.0 Brown |
| Quarter Loop  | Full Grain Buffalo Leather 1.8-2.0 Brown |
| Binding       | Pvc R 38 Brown Backing TPE 0.8 mm        |
| Quarter Label | Label Cheetah Tab TPR <b>Red</b>         |

### Lining

|                |                          |
|----------------|--------------------------|
| Vamp Lining    | Grey polyester Non Woven |
| Quarter Lining | Black Polyester Mesh     |

|                            |   |
|----------------------------|---|
| <b>Standard Compliance</b> | EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 |
| Toe Impact 200 Joules      | Clearance 22.08mm (> 14mm Std)            |
| Toe Compression 1500 N     | Clearance 23.26mm (>14mm Std)             |

### Miscellaneous

|               |                     |
|---------------|---------------------|
| Inner Counter | Thermoplastic sheet |
| Thread        | Thread Bonded Nylon |

### Outsole

|                              |   |
|------------------------------|---|
| Material                     | Nitrile   |
| Hardness                     | 65 - 70 Shore A 16.6 M $\Omega$ ( 0.1 – 1000 M $\Omega$ Std ) |
| Antistatic                   | Suitable  |
| Oil Resistance               | Suitable  |
| Acid & Alkali                | Suitable  |
| Vegetable Oil & Animal Fats  | Suitable  |
| Wet & Humid Condition        | Good  |
| Severe Surface Abrasion      | Good  |
| Heat Resistance (Short Term) | 300°C   |

- Steel toe protects from impact and compression**
- Strong and durable nitrile rubber outsole**
- Heat resistant up to 300 C**
- Acid and alkali resistant soles**
- PU Insole improves heel cushioning**



- \***additional steel midsole is available**
- \***available : custom label logo/emboss**

**Supplied & supported by Swarna Safety for industrial projects and export markets.**

# ADV™ JUBATUS 6112

High-compliance S3 safety boots for demanding industrial environments, featuring penetration resistance, water resistance, for long-term use with quick lace system

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**



- S3** support :
- **construction**
  - **mining (BEST)**
  - **oil & gas**

|                         |   |
|-------------------------|---|
| Brand                   | Cheetah                                 |
| Product Line            | ADV                                     |
| Product Name            | Jubatus Sand                            |
| Description             | Ankle Boots with Quick-Lace™            |
| Sizes                   | 4 - 12 ( UK )                           |
| Last                    | 701C                                    |
| Safety Toecap           | Composite                               |
| Nail Protection         | Solegard™ metal free nail-proof midsole |
| Insock                  | <b>AIRGO PUTM Comfort Insole</b>        |
| Weight (Approx. Size 7) | 665 grams                               |

### Upper Material

|                           |                                   |
|---------------------------|-----------------------------------|
| Vamp                      | Nubuck Leather 1.8-2.0 Sand       |
| Mudguard                  | Nubuck Leather 1.8-2.0 Sand       |
| Quarter                   | Nubuck Leather 1.8-2.0 Sand       |
| Lacing Eyestay            | Nubuck Leather 1.8-2.0 Sand       |
| Tongue Patch Top / Bottom | Nubuck Leather 1.8-2.0 Sand       |
| Toe bumper                | PU Coated Leather Black 1.8-2.0mm |
| Heel bumper               | PU Coated Leather Black 1.8-2.0mm |
| Eyelet/Lacing System      | Quick-Lace™ System                |
| Collar                    | Ripstop Black polyester           |
| Tongue                    | Ripstop Black polyester           |
| Quarter Window            | Ripstop Black polyester           |
| Emboss / Printing         | "ADV" Toe Bumper                  |

### Lining

|               |                            |
|---------------|----------------------------|
| Vamp Lining   | Grey polyester DryMax™     |
| Tongue Lining | goremesh polyester DryMax™ |
| Collar Lining | goremesh polyester         |

|                            |  |
|----------------------------|--|
| <b>Standard Compliance</b> | EN 20345 S3 SRC, ASTM F2413-11, SNI 7079 |
| Toe Impact 200 Joules      | Clearance 22.2mm (> 14mm Std)            |
| Toe Compression 1500 N     | Clearance 22.64mm (>14mm Std)            |

### Miscellaneous

|                |                              |
|----------------|------------------------------|
| Collar Padding | 24 mm Foam                   |
| Tongue padding | 8 mm Foam                    |
| Back strap     | 12mm Black/Silver reflective |
| Inner Counter  | Thermoplastic sheet          |
| Thread         | Thread Bonded Nylon          |

### Outsole

|                              |  |
|------------------------------|--|
| Material                     | Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68 |
| Hardness                     | Shore A ( Taupe )<br>Mid sole : 45 - 51 Shore A ( Black )                      |
| Antistatic                   | Yes<br>Dry: 312 MΩ ( 0.1 – 1000 MΩ Std )<br>Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std ) |
| Oil Resistance               | Suitable   |
| Acid & Alkali                | Not Suitable   |
| Vegetable Oil & Animal Fats  | Suitable   |
| Wet & Humid Condition        | Good   |
| Severe Surface Abrasion      | Good   |
| Heat Resistance (Short Term) | 150°C  |

- Lightweight composite toe protection**
- Enhanced shock absorption for all day comfort**
- Metal free nail-proof midsole**
- PU Insole improves heel cushioning**
- Water resistant upper keeps feet dry**



**\*available : custom label logo/emboss**

# ADV NYX 6012

Low-cut S3 safety shoes to enhanced mobility, suitable for professionals requiring safety compliance without compromising movement.

**S3**



support :

- construction
- mining (BEST)
- oil & gas



- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**

|                         |   |
|-------------------------|---|
| Brand                   | Cheetah                                 |
| Product Line            | ADV                                     |
| Product Name            | NYX                                     |
| Description             | Ankle Boots with Quick-Lace™ System     |
| Sizes                   | 4 – 12 ( UK )                           |
| Last                    | 701C                                    |
| Safety Toecap           | Composite                               |
| Nail Protection         | Solegard™ Metal free nail proof midsole |
| Insock                  | <b>AIRGO PUTM Comfort Insole</b>        |
| Weight (Approx. Size 7) | 651 grams                               |

### Upper Material

|                      |                                   |
|----------------------|-----------------------------------|
| Vamp                 | Nubuck Leather 1.8-2.0 Sand       |
| Mudguard             | Nubuck Leather 1.8-2.0 Sand       |
| Quarter              | Nubuck Leather 1.8-2.0 Sand       |
| Lacing Eyestay       | Nubuck Leather 1.8-2.0 Sand       |
| Tongue Patch Top     | Nubuck Leather 1.8-2.0 Sand       |
| Toe bumper           | PU Coated Leather Black 1.8-2.0mm |
| Heel bumper          | PU Coated Leather Black 1.8-2.0mm |
| Eyelet/Lacing System | Quick-Lace™ System                |
| Collar               | Ripstop Black polyester           |
| Tongue               | Ripstop Black polyester           |
| Quarter Window       | Ripstop Black polyester           |
| Emboss / Printing    | "ADV" Toe Bumper                  |

### Lining

|               |                             |
|---------------|-----------------------------|
| Vamp Lining   | Grey polyester DryMax™ gore |
| Tongue Lining | mesh polyester DryMax™ gore |
| Collar Lining | mesh polyester              |

|                            |  |
|----------------------------|--|
| <b>Standard Compliance</b> | EN 20345 S3 SRC, ASTM F2413-11, SNI 7079 |
| Toe Impact 200 Joules      | Clearance 22.2mm (> 14mm Std)            |
| Toe Compression 1500 N     | Clearance 22.64mm (>14mm Std)            |

### Miscellaneous

|                |                                   |
|----------------|-----------------------------------|
| Collar Padding | 24 mm Foam                        |
| Tongue padding | 8 mm Foam                         |
| Webbing        | 12mm Black/Silver Reflective      |
| Insole         | Ibisafe 31 Conductive White 2.8mm |
| Inner Counter  | Thermoplastic sheet               |
| Thread         | Thread Bonded Nylon               |

### Outsole

|                              |  |
|------------------------------|--|
| Material                     | Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68 |
| Hardness                     | Shore A<br>Mid sole : 45 - 51 Shore A  |
| Antistatic                   | Yes<br>Dry: 312 MΩ ( 0.1 – 1000 MΩ Std )<br>Wet: 21.7 MΩ ( 0.1 – 1000 MΩ Std ) |
| Oil Resistance               | Suitable   |
| Acid & Alkali                | Not Suitable   |
| Vegetable Oil & Animal Fats  | Suitable   |
| Wet & Humid Condition        | Good   |
| Severe Surface Abrasion      | Good   |
| Heat Resistance (Short Term) | 150°C  |



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



**\*available : custom label logo/emboss**

# NITRILE 2290

Specialized **welding** safety boots designed with heat-resistant outsole and protective upper construction to reduce exposure to sparks, molten metal, and hot debris.



## S1/S1P\*

support :

- **construction**
- **mining**
- **oil & gas**

- **Nitrile Rubber**
- **Heat Resistant (Up to 300 C)**
- **Steel SafetyToe**
- **Chemical Resistant Outsole**

|                         |  |
|-------------------------|--|
| Brand                   | Cheetah                                    |
| Product Line            | Nitrile                                    |
| Description             | Welder Boots with adjustable velcro straps |
| Sizes                   | 4 – 12 ( UK )                              |
| Last                    | 130  |
| Safety Toecap           | Steel                                      |
| Nail Protection         | Optional                                   |
| Sole                    | Nitrile                                    |
| Insock                  | AIRGO PUTM Comfort Insole                  |
| Weight (Approx. Size 7) | 750 grams                                  |

### Upper Material

|              |  |
|--------------|--|
| Vamp         | Buffalo Suede Leather 1.8-2.0 mm Black |
| Quarter      | Buffalo Suede Leather 1.8-2.0 mm Black |
| Back strap   | Buffalo Suede Leather 1.8-2.0 mm Black |
| Back Counter | Buffalo Suede Leather 1.8-2.0 mm Black |
| Strap In     | Buffalo Suede Leather 1.8-2.0 mm Black |
| Strap Out    | Buffalo Suede Leather 1.8-2.0 mm Black |
| Tongue       | Buffalo Suede Leather 1.0-1.2 mm Black |

### Lining

|                |                          |
|----------------|--------------------------|
| Vamp Lining    | Grey polyester Non Woven |
| Quarter Lining | Black Polyester Mesh     |

|                            |   |
|----------------------------|---|
| <b>Standard Compliance</b> | EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 |
| Toe Impact 200 Joules      | Clearance 22.08mm (> 14mm Std)            |
| Toe Compression 1500 N     | Clearance 23.26mm (>14mm Std)             |

### Miscellaneous

|                       |                             |
|-----------------------|-----------------------------|
| Inner Counter         | Thermoplastic sheet         |
| <b>Reflective</b>     | Reflective Silver           |
| <b>Velcro</b>         | Velcro Hook / Loop          |
| <b>Collar Padding</b> | 24 mm Foam Density 30       |
| Webbing               | Webbing Cheetah Black / Red |
| Thread                | Thread Bonded Nylon         |

### Outsole

|                              |                               |
|------------------------------|-------------------------------|
| Material                     | Nitrile                       |
| Hardness                     | 65 - 70 Shore A               |
| Antistatic                   | 16.6 MΩ ( 0.1 – 1000 MΩ Std ) |
| Oil Resistance               | Suitable                      |
| Acid & Alkali                | Suitable                      |
| Vegetable Oil & Animal Fats  | Suitable                      |
| Wet & Humid Condition        | Good                          |
| Severe Surface Abrasion      | Good                          |
| Heat Resistance (Short Term) | 300°C                         |

- \*additional steel midsole is available
- \*available : custom label logo/emboss

-  **Steel toe protects from impact and compression**
-  **Strong and durable nitrile rubber outsole**
-  **Heat resistant up to 300 C**
-  **Acid and alkali resistant soles**
-  **PU Insole improves heel cushioning**

