

product catalogue



SWARNA SAFETY

PT Swarna Muda Global

swarnasafety.com | (+62) 851-2137-1497

info@swarnasafety.com



CALIFORNIA S1 class

6" Lace-up Ankle Boot with Padded Topline

designed & developed
in Australia
(AS/NZS) CERTIFIED



Lightweight



COOLMAX®
lining



Dual density
TPU/PU direct
injection sole



Flexible insole



Buffalo full grain
leather upper



SRC



200J & 15KN
compression
steel toecap



Sizes: 4-12
(includes half sizes)

products certification :



Supplied by Swarna Safety
for export markets



GRASBERG S1 class

6" Zip-sided Mining Boot with Scuff Cap

designed & developed
in Australia
(AS/NZS) CERTIFIED



Lightweight



COOLMAX®
lining



Dual density
TPU/PU direct
injection sole



Flexible insole



Buffalo full grain
leather upper



SRC



200J & 15KN
compression
steel toecap



Sizes: 4-12
(includes half sizes)

products certification :



OREGON S1 class

9" Pull-on Riggers Boot

designed & developed
in Australia
(AS/NZS) CERTIFIED



Lightweight



COOLMAX®
lining



Dual density
TPU/PU direct
injection sole



Flexible insole



Buffalo full grain
leather upper



SRC



200J & 15KN
compression
steel toecap



Sizes: 4-12
(includes half sizes)

products certification :



MONTANA S1 class

6" Elastic-sided Boot

designed & developed
in Australia
(AS/NZS) CERTIFIED



Lightweight



COOLMAX®
lining



Dual density
TPU/PU direct
injection sole



Flexible insole



Buffalo full grain
leather upper



SRC



200J & 15KN
compression
steel toecap



Sizes: 4-12
(includes half sizes)

products certification :



COLORADO S1 class

6" Lace-up Ankle Boot with Padded Topline

designed & developed
in Australia
(AS/NZS) CERTIFIED



Lightweight



COOLMAX®
lining



Dual density
TPU/PU direct
injection sole



Flexible insole



Buffalo full grain
leather upper



SRC



200J & 15KN
compression
steel toecap



Sizes: 4-12
(includes half sizes)

products certification :



Supplied by Swarna Safety
for export markets



need quotation or product advisory?

 swarnasafety.com

 (+62) 851-2137-1497

 info@swarnasafety.com



SWARNA SAFETY
PT Swarna Muda Global

swarnasafety.com | (+62) 851-2137-1497
info@swarnasafety.com

OIL & GAS safety shoes

PRODUCT SHEET



NITRILE 2288

Heavy-duty safety boots equipped with nitrile rubber outsole, high heat resistance, and superior oil and chemical resistance for extreme industrial environments.



S1/S1P*



support :

- construction
- mining
- oil & gas (BEST)

- Nitrile Rubber
- Steel SafetyToe
- Heat Resistant (Up to 300 C)
- Chemical Resistant Outsole

Brand	Cheetah
Product Line	Nitrile
Product Name	Nitrile
Description	Pull Up " Rigger " Boots
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	800 grams

Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back Counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Binding	Pvc R 38 Brown Backing TPE 0.8 mm
Quarter Label	Label Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A 16.6 M Ω (0.1 – 1000 M Ω Std)
Antistatic	Suitable
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



Steel toe protects from impact and compression



Strong and durable nitrile rubber outsole



Heat resistant up to 300 C



Acid and alkali resistant soles



PU Insole improves heel cushioning



- *additional steel midsole is available
- *available : custom label logo/emboss

Supplied & supported by Swarna Safety for industrial projects and export markets.

ADV™ JUBATUS 6112

High-compliance S3 safety boots for demanding industrial environments, featuring penetration resistance, water resistance, for long-term use with quick lace system

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**



- S3** support :
- **construction**
 - **mining (BEST)**
 - **oil & gas**

Brand	Cheetah
Product Line	ADV
Product Name	Jubatus Sand
Description	Ankle Boots with Quick-Lace™
Sizes	4 - 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	665 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top / Bottom	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™
Tongue Lining	goremesh polyester DryMax™
Collar Lining	goremesh polyester

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Back strap	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A (Taupe) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

- Lightweight composite toe protection**
- Enhanced shock absorption for all day comfort**
- Metal free nail-proof midsole**
- PU Insole improves heel cushioning**
- Water resistant upper keeps feet dry**



***available : custom label logo/emboss**

Supplied & supported by Swarna Safety for industrial projects and export markets.

NITRILE 2290

Specialized **welding** safety boots designed with heat-resistant outsole and protective upper construction to reduce exposure to sparks, molten metal, and hot debris.



S1/S1P*

support :

- **construction**
- **mining**
- **oil & gas**

- **Nitrile Rubber**
- **Steel SafetyToe**
- **Heat Resistant (Up to 300 C)**
- **Chemical Resistant Outsole**

Brand	Cheetah
Product Line	Nitrile
Description	Welder Boots with adjustable velcro straps
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	750 grams

Upper Material

Vamp	Buffalo Suede Leather 1.8-2.0 mm Black
Quarter	Buffalo Suede Leather 1.8-2.0 mm Black
Back strap	Buffalo Suede Leather 1.8-2.0 mm Black
Back Counter	Buffalo Suede Leather 1.8-2.0 mm Black
Strap In	Buffalo Suede Leather 1.8-2.0 mm Black
Strap Out	Buffalo Suede Leather 1.8-2.0 mm Black
Tongue	Buffalo Suede Leather 1.0-1.2 mm Black

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Reflective	Reflective Silver
Velcro	Velcro Hook / Loop
Collar Padding	24 mm Foam Density 30
Webbing	Webbing Cheetah Black / Red
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

- *additional steel midsole is available
- *available : custom label logo/emboss

- Steel toe protects from impact and compression
- Strong and durable nitrile rubber outsole
- Heat resistant up to 300 C
- Acid and alkali resistant soles
- PU insole improves heel cushioning



ADV NYX 6012

Low-cut S3 safety shoes to enhanced mobility, suitable for professionals requiring safety compliance without compromising movement.



S3



support :

- construction
- mining (BEST)
- oil & gas

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**

Brand	Cheetah
Product Line	ADV
Product Name	NYX
Description	Ankle Boots with Quick-Lace™ System
Sizes	4 – 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free nail proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	651 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™ gore
Tongue Lining	mesh polyester DryMax™ gore
Collar Lining	mesh polyester

Standard Compliance

	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Webbing	12mm Black/Silver Reflective
Insole	Ibisafe 31 Conductive White 2.8mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Metal free nail-proof midsole



PU Insole improves heel cushioning



Water resistant upper keeps feet dry



***available : custom label logo/emboss**

REBOUND 7106 H

Designed for daily industrial use, combining steel toe protection, durable full grain leather, and dual density PU outsole to **support long working hours on mixed surfaces.**



S1/S1P*

support :

- **construction (BEST)**
- **mining**
- **oil & gas**

- **DoublePU Outsole**
- **Steel Midsole (Optional)**
- **Steel Safety Toe**
- **Durable Grain Upper**

Brand	CHEETAH
Product Line	Rebound
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	667 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Tongue	Full Grain Buffalo Leather 1.0-1.2 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Accesoris	D Ring
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A (Gray) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



***additional steel midsole is available (S1P edition)**

***available : custom label logo/emboss**

CONSTRUCTION safety shoes

PRODUCT SHEET



REBOUND 7106 H

Designed for daily industrial use, combining steel toe protection, durable full grain leather, and dual density PU outsole to **support long working hours on mixed surfaces.**



✓ support :

- **construction (BEST)**
- **mining**
- **oil & gas**

S1/S1P*

- **DoublePU Outsole**
- **Steel Midsole (Optional)**
- **SteelSafety Toe**
- **Durable Grain Upper**

Brand	CHEETAH
Product Line	Rebound
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	667 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Tongue	Full Grain Buffalo Leather 1.0-1.2 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)


Miscellaneous


Collar Padding	24 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Accesoris	D Ring
Thread	Thread Bonded Nylon


Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A (Gray) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

 **Steel toe protects from impact and compression**

 **Enhanced shock absorption for all day comfort**

 **Durable and long-lasting genuine leather upper**

 **Improved slip resistance**



***additional steel midsole is available (S1P edition)**

***available : custom label logo/emboss**

REBOUND 7288

Traditional rigger-style safety boots featuring pull-on design, steel toe protection, and robust leather construction for outdoor industrial work.



S1/S1P*



support :

- construction (BEST)
- mining
- oil & gas

- DoublePU Outsole
- Steel Midsole (Optional)
- SteelSafety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Pull up 'Rigger' Boots
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
Weight (Size 7 half pair)	705 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Top Binding	Pvc R 38 Brown Backing TPE 0.8
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Black
Hardness	Out sole : 62 - 68 Shore A (Black) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



*additional steel midsole is available (S1P edition)

*available : custom label logo/emboss

REBOUND 7110 H

Slip-on safety shoes engineered for convenience and efficiency, offering steel toe protection with easy on-off functionality for supervisory and inspection roles.



S1/S1P*

support :

- construction
- mining
- oil & gas

- DoublePU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Pull up ankle boots with elastic sides
Sizes	4 – 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Sole	Dual PU Antistatic
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	580 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Black
Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Black
Back counter	Full Grain Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Elastic / Gore	5 Inch Elastic Black
Webbing	Cheetah 20 mm Black/Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Gray
Hardness	Out sole : 62 - 68 Shore A (Gray) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



- *additional steel midsole is available
- *available : custom label logo/emboss

NITRILE 2288

Heavy-duty safety boots equipped with nitrile rubber outsole, high heat resistance, and superior oil and chemical resistance for extreme industrial environments.



S1/S1P*



support :

- construction
- mining
- oil & gas (BEST)

- Nitrile Rubber
- Steel SafetyToe
- Heat Resistant (Up to 300 C)
- Chemical Resistant Outsole

Brand	Cheetah
Product Line	Nitrile
Product Name	Nitrile
Description	Pull Up " Rigger " Boots
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	800 grams

Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back Counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Binding	Pvc R 38 Brown Backing TPE 0.8 mm
Quarter Label	Label Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A 16.6 M Ω (0.1 – 1000 M Ω Std)
Antistatic	Suitable
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C



Steel toe protects from impact and compression



Strong and durable nitrile rubber outsole



Heat resistant up to 300 C



Acid and alkali resistant soles



PU Insole improves heel cushioning



- *additional steel midsole is available
- *available : custom label logo/emboss

Supplied & supported by Swarna Safety for industrial projects and export markets.

REVOLUTION 3180

Affordable ankle-height safety boots offering **basic protection** and improved ankle support for general industrial use.



S1/S1P*

support :

- **construction**
- **warehouse**
- **office**

- **Single PU Outsole**
- **Steel Midsole (Optional)**
- **Steel Safety Toe**
- **Economical Pricing**

Brand	CHEETAH
Product Line	Revolution
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

UpperMaterial

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ (0.1 – 1000 MΩ Std) Wet: 20.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Slip resistant outsole



- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

NITRILE 2290

Specialized **welding** safety boots designed with heat-resistant outsole and protective upper construction to reduce exposure to sparks, molten metal, and hot debris.



S1/S1P*

support :

- **construction**
- **mining**
- **oil & gas**

- **Nitrile Rubber**
- **Heat Resistant (Up to 300 C)**
- **Steel SafetyToe**
- **Chemical Resistant Outsole**

Brand	Cheetah
Product Line	Nitrile
Description	Welder Boots with adjustable velcro straps
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	750 grams

Upper Material

Vamp	Buffalo Suede Leather 1.8-2.0 mm Black
Quarter	Buffalo Suede Leather 1.8-2.0 mm Black
Back strap	Buffalo Suede Leather 1.8-2.0 mm Black
Back Counter	Buffalo Suede Leather 1.8-2.0 mm Black
Strap In	Buffalo Suede Leather 1.8-2.0 mm Black
Strap Out	Buffalo Suede Leather 1.8-2.0 mm Black
Tongue	Buffalo Suede Leather 1.0-1.2 mm Black

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Reflective	Reflective Silver
Velcro	Velcro Hook / Loop
Collar Padding	24 mm Foam Density 30
Webbing	Webbing Cheetah Black / Red
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

-  Steel toe protects from impact and compression
-  Strong and durable nitrile rubber outsole
-  Heat resistant up to 300 C
-  Acid and alkali resistant soles
-  PU insole improves heel cushioning



Supplied & supported by Swarna Safety for industrial projects and export markets.

MINING safety shoes

PRODUCT SHEET



ADV™ JUBATUS 6112

High-compliance S3 safety boots for demanding industrial environments, featuring penetration resistance, water resistance, for long-term use with quick lace system

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**



- S3** support :
- **construction**
 - **mining (BEST)**
 - **oil & gas**

Brand	Cheetah
Product Line	ADV
Product Name	Jubatus Sand
Description	Ankle Boots with Quick-Lace™
Sizes	4 - 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	665 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top / Bottom	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™
Tongue Lining	goremesh polyester DryMax™
Collar Lining	goremesh polyester

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Back strap	12mm Black/Silver reflective
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A (Taupe) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

- Lightweight composite toe protection**
- Enhanced shock absorption for all day comfort**
- Metal free nail-proof midsole**
- PU Insole improves heel cushioning**
- Water resistant upper keeps feet dry**



***available : custom label logo/emboss**

Supplied & supported by Swarna Safety for industrial projects and export markets.

ADV NYX 6012

Low-cut S3 safety shoes to enhanced mobility, suitable for professionals requiring safety compliance without compromising movement.



S3



support :

- construction
- mining (BEST)
- oil & gas

- **DoublePU Outsole**
- **Composite Safety Toe**
- **SoleGard™**
- **Water Resistant**

Brand	Cheetah
Product Line	ADV
Product Name	NYX
Description	Ankle Boots with Quick-Lace™ System
Sizes	4 – 12 (UK)
Last	701C
Safety Toecap	Composite
Nail Protection	Solegard™ Metal free nail proof midsole
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	651 grams

Upper Material

Vamp	Nubuck Leather 1.8-2.0 Sand
Mudguard	Nubuck Leather 1.8-2.0 Sand
Quarter	Nubuck Leather 1.8-2.0 Sand
Lacing Eyestay	Nubuck Leather 1.8-2.0 Sand
Tongue Patch Top	Nubuck Leather 1.8-2.0 Sand
Toe bumper	PU Coated Leather Black 1.8-2.0mm
Heel bumper	PU Coated Leather Black 1.8-2.0mm
Eyelet/Lacing System	Quick-Lace™ System
Collar	Ripstop Black polyester
Tongue	Ripstop Black polyester
Quarter Window	Ripstop Black polyester
Emboss / Printing	"ADV" Toe Bumper

Lining

Vamp Lining	Grey polyester DryMax™ gore
Tongue Lining	mesh polyester DryMax™ gore
Collar Lining	mesh polyester

Standard Compliance	EN 20345 S3 SRC, ASTM F2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.64mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam
Tongue padding	8 mm Foam
Webbing	12mm Black/Silver Reflective
Insole	Ibisafe 31 Conductive White 2.8mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Taupe With TPU Red Insert Out sole : 62 - 68
Hardness	Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

- Lightweight composite toe protection
- Enhanced shock absorption for all day comfort
- Metal free nail-proof midsole
- PU Insole improves heel cushioning
- Water resistant upper keeps feet dry



***available : custom label logo/emboss**

Supplied & supported by Swarna Safety for industrial projects and export markets.

NITRILE 2288

Heavy-duty safety boots equipped with **nitrile rubber** outsole, **high heat resistance**, and superior oil and chemical resistance for extreme industrial environments.



S1/S1P*

support :

- **construction**
- **mining**
- **oil & gas (BEST)**

- **Nitrile Rubber** • **Heat Resistant (Up to 300 C)**
- **Steel SafetyToe** • **Chemical Resistant Outsole**

Brand	Cheetah
Product Line	Nitrile
Product Name	Nitrile
Description	Pull Up " Rigger " Boots
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	800 grams

Upper Material

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back Counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Binding	Pvc R 38 Brown Backing TPE 0.8 mm
Quarter Label	Label Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A 16.6 MQ (0.1 – 1000 MQ Std)
Antistatic	Suitable
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

- Steel toe protects from impact and compression**
- Strong and durable nitrile rubber outsole**
- Heat resistant up to 300 C**
- Acid and alkali resistant soles**
- PU Insole improves heel cushioning**



Supplied & supported by Swarna Safety for industrial projects and export markets.

NITRILE 2290

Specialized **welding** safety boots designed with heat-resistant outsole and protective upper construction to reduce exposure to sparks, molten metal, and hot debris.



S1/S1P*

support :

- **construction**
- **mining**
- **oil & gas**

- **Nitrile Rubber**
- **Steel SafetyToe**
- **Heat Resistant (Up to 300 C)**
- **Chemical Resistant Outsole**

Brand	Cheetah
Product Line	Nitrile
Description	Welder Boots with adjustable velcro straps
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Sole	Nitrile
Insock	AIRGO PUTM Comfort Insole
Weight (Approx. Size 7)	750 grams

Upper Material

Vamp	Buffalo Suede Leather 1.8-2.0 mm Black
Quarter	Buffalo Suede Leather 1.8-2.0 mm Black
Back strap	Buffalo Suede Leather 1.8-2.0 mm Black
Back Counter	Buffalo Suede Leather 1.8-2.0 mm Black
Strap In	Buffalo Suede Leather 1.8-2.0 mm Black
Strap Out	Buffalo Suede Leather 1.8-2.0 mm Black
Tongue	Buffalo Suede Leather 1.0-1.2 mm Black

Lining

Vamp Lining	Grey polyester Non Woven
Quarter Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 22.08mm (> 14mm Std)
Toe Compression 1500 N	Clearance 23.26mm (>14mm Std)

Miscellaneous

Inner Counter	Thermoplastic sheet
Reflective	Reflective Silver
Velcro	Velcro Hook / Loop
Collar Padding	24 mm Foam Density 30
Webbing	Webbing Cheetah Black / Red
Thread	Thread Bonded Nylon

Outsole

Material	Nitrile
Hardness	65 - 70 Shore A
Antistatic	16.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	300°C

- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

-  **Steel toe protects from impact and compression**
-  **Strong and durable nitrile rubber outsole**
-  **Heat resistant up to 300 C**
-  **Acid and alkali resistant soles**
-  **PU insole improves heel cushioning**



REBOUND 7288

Traditional rigger-style safety boots featuring pull-on design, steel toe protection, and robust leather construction for outdoor industrial work.



S1/S1P*



support :

- construction (BEST)
- mining
- oil & gas

- DoublePU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Pull up 'Rigger' Boots
Sizes	4 - 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
Weight (Size 7 half pair)	705 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Top Binding	Pvc R 38 Brown Backing TPE 0.8
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 Clearance 16.5 mm (> 14mm Std)
Toe Impact 200 Joules	mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Black
Hardness	Out sole : 62 - 68 Shore A (Black) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 - 1000 MΩ Std) Wet: 21.7 MΩ (0.1 - 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



*additional steel midsole is available (S1P edition)

*available : custom label logo/emboss

REBOUND 7288

Traditional rigger-style safety boots featuring pull-on design, steel toe protection, and robust leather construction for outdoor industrial work.



S1/S1P*



support :

- construction (BEST)
- mining
- oil & gas

- DoublePU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Durable Grain Upper

Brand	CHEETAH
Product Line	Rebound
Description	Pull up 'Rigger' Boots
Sizes	4 - 12 (UK)
Last	701S
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
Weight (Size 7 half pair)	705 grams

UpperMaterial

Vamp	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter IN	Full Grain Buffalo Leather 1.8-2.0 Brown
Front Quarter Out	Full Grain Buffalo Leather 1.8-2.0 Brown
Rear Quarter	Full Grain Buffalo Leather 1.8-2.0 Brown
Back counter	Full Grain Buffalo Leather 1.8-2.0 Brown
Quarter Loop	Full Grain Buffalo Leather 1.8-2.0 Brown
Top Binding	Pvc R 38 Brown Backing TPE 0.8
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079 Clearance 16.5 mm (> 14mm Std)
Toe Impact 200 Joules	mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Inner counter	Thermoplastic heel counter
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Black
Hardness	Out sole : 62 - 68 Shore A (Black) Mid sole : 45 - 51 Shore A (Black)
Antistatic	Yes Dry: 312 MΩ (0.1 - 1000 MΩ Std) Wet: 21.7 MΩ (0.1 - 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Enhanced shock absorption for all day comfort



Durable and long-lasting genuine leather upper



Improved slip resistance



*additional steel midsole is available (S1P edition)

*available : custom label logo/emboss

warehouse

(indoor)

safety shoes



REVOLUTION 3180

Affordable ankle-height safety boots offering **basic protection** and improved ankle support for general industrial use.



S1/S1P*

support :

- **construction**
- **warehouse**
- **office**

- **Single PU Outsole**
- **Steel Midsole (Optional)**
- **Steel Safety Toe**
- **Economical Pricing**

Brand	CHEETAH
Product Line	Revolution
Description	Mid Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

UpperMaterial

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ (0.1 – 1000 MΩ Std) Wet: 20.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Slip resistant outsole



- ***additional steel midsole is available**
- ***available : custom label logo/emboss**

REVOLUTION 3002 H

Affordable low-cut safety shoes providing essential protection and comfort for general industrial, warehouse, and support operations.



S1/S1P*

support :

- construction
- warehouse
- office

- Single PU Outsole
- Steel Midsole (Optional)
- Steel Safety Toe
- Economical Pricing

Brand	CHEETAH
Product Line	Revolution
Description	Low Cut Lace Up Shoes
Sizes	4 – 12 (UK)
Last	130
Safety Toecap	Steel
Nail Protection	Optional
Insock	Eva Foam, 7 mm
ESD/Antistatic	Antistatic
Weight (Approx. Size 7)	495 grams

Upper Material

Vamp	Split Buffalo Leather 1.8-2.0 Black
Quarter IN	Split Buffalo Leather 1.8-2.0 Black
Quarter Out	Split Buffalo Leather 1.8-2.0 Black
Back counter	Split Buffalo Leather 1.8-2.0 Black
Collar	Pvc R 38 Black Backing TPE 0.8
Tongue	Pvc R 38 Black Backing TPE 0.8
Tongue Logo	"Animal CHEETAH " Polyester Label
Quarter Label	Cheetah Tab TPR Red

Lining

Vamp Lining	Grey polyester Non Woven
Tongue Lining	Black Polyester Mesh Black
Quarter/Collar Lining	Polyester Mesh

Standard Compliance	EN 20345 S1 SRC, ASTM F-24 2011, SNI 7079
Toe Impact 200 Joules	Clearance 16.5 mm (> 14mm Std)
Toe Compression 1500 N	Clearance 20.5 mm (>14mm Std)

Miscellaneous

Collar Padding	24 mm Foam Density 30
Tongue Padding	8 mm Foam Density 30
Lace	Lace Ø 4.0 mm Black
Inner counter	Thermoplastic heel counter
Eyelet	Hexagonal
Thread	Thread Bonded Nylon

Outsole

Material	Single Density Polyurethane Black
Hardness	57- 63 Shore A
Antistatic	Yes Dry: 264 MΩ (0.1 – 1000 MΩ Std) Wet: 20.6 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C

- *additional steel midsole is available
- *available : custom label logo/emboss



Steel toe protects from impact and compression



Flexible and light to reduce fatigue



Slip resistant outsole



CHEETAH
Reflex™ 8083

Lightweight low-cut safety shoes featuring breathable materials for improved airflow, all-day comfort, and reliable protection in indoor and light industrial environments.

S1/S1P*

support :

- construction
- warehouse
- office



- DoublePU Outsole • Composite Safety Toe
- SoleGard™ • Water Resistant

Brand	Cheetah
Product Line	Reflex
Product Name	Reflex 8083
Description	Lace up Sport Safety Shoes
Sizes	5 – 12 (UK)
Last	701 F
Safety Toecap	Composite Fiberglass
Nail Protection	Solegard™ metal free nail-proof midsole
Insock	Insock Foam Red Black 150
Weight (Approx. Size 7)	498 grams

Upper Material

Vamp	Textile Knit Upper Cheetah Grey
Eyestay	Danaces Black Translucent Danaces
Eyestay Backer	Black Translucent
Toe bumper	PU Coated Leather Black 1.8-2.0 mm
Heel bumper	PU Coated Leather Black 1.8-2.0 mm
Lace	Lace 5mm Lime
Webbing	20 mm CHEETAH Black / Lime
Reinforce	Nonwoven Black
Emboss / Printing	" R " Toe Bumper

Lining

Vamp Lining	Grey polyester
Tongue Lining	Black Polyester Mesh
Collar Lining	Black Polyester Mesh

Standard Compliance	EN 20345 S1 P SRC, ASTM F-2413-11, SNI 7079
Toe Impact 200 Joules	Clearance 22.2mm (> 14mm Std)
Toe Compression 1500 N	Clearance 22.6mm (>14mm Std)

Miscellaneous

Collar Padding	8 mm Foam
Insole	Ibisafe 31 Conductive White 3.6mm
Inner Counter	Thermoplastic sheet
Thread	Thread Bonded Nylon

Outsole

Material	Dual Density Polyurethane Black / Lime
Hardness	Out sole : 62 - 68 Shore A Mid sole : 45 - 51 Shore A
Antistatic	Yes Dry: 312 MΩ (0.1 – 1000 MΩ Std) Wet: 21.7 MΩ (0.1 – 1000 MΩ Std)
Oil Resistance	Suitable
Acid & Alkali	Not Suitable
Vegetable Oil & Animal Fats	Suitable
Wet & Humid Condition	Good
Severe Surface Abrasion	Good
Heat Resistance (Short Term)	150°C



Lightweight composite toe protection



Enhanced shock absorption for all day comfort



Nail Proof SoleGard™ Midsole



PU Insole improves heel cushioning



Breathable AirKnit™ Upper



need quotation or product advisory?

 swarnasafety.com

 (+62) 851-2137-1497

 info@swarnasafety.com